



### Colorimetric Parameters

Chromaticity Coordinate:  $x=0.3401$   $y=0.3437$  /  $u'=0.2111$   $v'=0.4800$

CCT=5173K (Duv=-0.0020) Dominant WL:  $L_d = 573.0$ nm Purity=5.2%

Peak WL:  $L_p = 450.3$ nm FWHM=18.4nm

Render Index:  $R_a = 95.7$  Render Index: AvgR = 93.3

R1 = 95	R2 = 98	R3 = 98	R4 = 94	R5 = 95	R6 = 96	R7 = 98	
R8 = 92	R9 = 77	R10 = 95	R11 = 91	R12 = 85	R13 = 96	R14 = 99	R15 = 93

### Photometric & Radiometric Parameters

Flux=228.5 lm Eff.:78.61 lm/W  $F_e = 928.9$  mW

### Electrical parameters

V=24.00 V I=0.1211 A P=2.906 W PF=1.000 F=0.00 Hz

LEVEL:OUT WHITE:ANSI\_5000K

Status: Integral T = 72 ms  $I_p = 48774$  (74%)

Test Mode: Accuracy Test; Sensitivity = High; Tecool: ON

Model: XFL-HD-2403-70022-5095-SP005	Number: 1
Test By: ***	Date: 2020-06-09 14:14:15
Temperature: 23Deg	Humidity: 55%
Manufacturer:	Remarks:
Assessor: damin	Device:

# TM30

