



Colorimetric Parameters

Chromaticity Coordinate: $x=0.3438$ $y=0.3469$ / $u'=0.2124$ $v'=0.4821$
 CCT=5037K (Duv=-0.0019) Dominant WL: $L_d = 574.9\text{nm}$ Purity=7.2%
 Peak WL: $L_p=449.9\text{nm}$ FWHM=18.7nm
 Render Index: $R_a=95.5$ Render Index: AvgR =93.1
 R1 =95 R2 =97 R3 =98 R4 =94 R5 =95 R6 =96 R7 =98
 R8 =91 R9 =76 R10=94 R11=91 R12=86 R13=95 R14=99 R15=92

Photometric & Radiometric Parameters

Flux=354.4 lm Eff.:77.24 lm/W $F_e=1.446$ W

Electrical parameters

V=24.00 V I=0.1912 A P=4.588 W PF=1.000 F=0.00 Hz

LEVEL:OUT WHITE:ANSI_5000K

Status: Integral T = 46 ms $I_p = 48941$ (75%)
 Test Mode: Accuracy Test; Sensitivity = High; Tecool: ON

Model: XFL-HD-2404-70022-5095-SP005 Number: 6
 Test By: *** Date: 2020-06-23 10:49:40
 Temperature: 23Deg Humidity: 55%
 Manufacturer:
 Assessor: damin DeviceSN:

TM30

