



Colorimetric Parameters

Chromaticity Coordinate: $x=0.4271$ $y=0.3817$ / $u'=0.2540$ $v'=0.5108$
 CCT=2982K (Duv=-0.0078) Dominant WL: $L_d = 586.3\text{nm}$ Purity=42.7%
 Peak WL: $L_p = 615.2\text{nm}$ FWHM=143.7nm
 Render Index: $R_a = 93.0$ Render Index: AvgR =91.1
 R1 =98 R2 =96 R3 =96 R4 =98 R5 =97 R6 =89 R7 =88
 R8 =82 R9 =64 R10=94 R11=93 R12=82 R13=96 R14=99 R15=95

Photometric & Radiometric Parameters

Flux=209.2 lm Eff.:66.05 lm/W $F_e = 703.8$ mW

Electrical parameters

V=24.00 V I=0.1320 A P=3.168 W PF=1.000 F=0.00 Hz

LEVEL:OUT WHITE:OUT

Status: Integral T = 50 ms $I_p = 49425$ (75%)

Test Mode: Accuracy Test; Sensitivity = High; Tecool: ON

Model: XFL-SE-2403-12022-3095-SP005 Number:18
 Test By:*** Date:2020-06-12 17:25:38
 Temperature:23Deg Humidity:55%
 Manufacturer: Remarks:
 Assessor:damin

TM30

