



### Colorimetric Parameters

Chromaticity Coordinate:  $x=0.4412$   $y=0.4004$   $u'=0.2550$   $v'=0.5206$   
 CCT=2899K (Duv=-0.0020) Dominant WL:Ld =584.0nm Purity=52.6%  
 Peak WL:Lp=632.9nm FWHM=122.1nm  
 Render Index:Ra=97.3 Render Index:AvgR =96.3  
 R1 =96 R2 =98 R3 =97 R4 =96 R5 =97 R6 =96 R7 =99  
 R8 =99 R9 =97 R10=98 R11=93 R12=87 R13=96 R14=97 R15=97

### Photometric & Radiometric Parameters

Flux=108.2 lm Eff.:82.85 lm/W Fe=415.9 mW

### Electrical parameters

V=24.00 V I=0.05440 A P=1.305 W PF=1.000 F=0.00 Hz

LEVEL:OUT WHITE:ANSI\_3000K

Status: Integral T = 85 ms Ip = 48820 (74%)

Test Mode: Accuracy Test; Sensitivity = High; Tecool: ON

Model:XFL-SW-2401-24022-3095-SP005 Number:3  
 Test By:\*\*\* Date:2020-06-29 13:34:07  
 Temperature:23Deg Humidity:55%  
 Manufacturer:  
 Assessor:damin

## TM30

