



### Colorimetric Parameters

Chromaticity Coordinate:  $x=0.4387$   $y=0.4033$   $u'=0.2520$   $v'=0.5213$   
 CCT=2964K (Duv=-0.0006) Dominant WL:Ld =583.2nm Purity=52.7%  
 Peak WL:Lp=647.7nm FWHM=189.8nm  
 Render Index:Ra=96.7 Render Index:AvgR =96.5  
 R1 =99 R2 =98 R3 =95 R4 =93 R5 =98 R6 =98 R7 =96  
 R8 =97 R9 =98 R10=96 R11=91 R12=93 R13=100 R14=97 R15=99

### Photometric & Radiometric Parameters

Flux=79.18 lm Eff.:57.68 lm/W Fe=324.4 mW

### Electrical parameters

V=24.00 V I=0.05720 A P=1.373 W PF=1.000 F=0.00 Hz

LEVEL:OUT WHITE:ANSI\_3000K

Status: Integral T = 147 ms Ip = 48737 (74%)  
 Test Mode: Accuracy Test; Sensitivity = High; Tecool: ON

Model:XFL-TW-2409-24022-22/3095-SPN005  
 Test By:\*\*\* Date:2020-06-12 16:37:44  
 Temperature:23Deg Humidity:55%  
 Manufacturer: Remarks:  
 Assessor:damin

## TM30

