



### Colorimetric Parameters

Chromaticity Coordinate:  $x=0.4374$   $y=0.4020$   $u'=0.2518$   $v'=0.5206$   
 CCT=2975K (Duv=-0.0009) Dominant WL:Ld =583.3nm Purity=51.9%  
 Peak WL:Lp=647.7nm FWHM=190.3nm  
 Render Index:Ra=96.7 Render Index:AvgR =96.5  
 R1 =99 R2 =98 R3 =95 R4 =93 R5 =98 R6 =98 R7 =96  
 R8 =97 R9 =98 R10=96 R11=91 R12=94 R13=100 R14=97 R15=99

### Photometric & Radiometric Parameters

Flux=126.4 lm Eff.:55.10 lm/W Fe=517.5 mW

### Electrical parameters

V=24.00 V I=0.09560 A P=2.294 W PF=1.000 F=0.00 Hz

LEVEL:OUT WHITE:ANSI\_3000K

Status: Integral T = 92 ms Ip = 48637 (74%)

Test Mode: Accuracy Test; Sensitivity = High; Tecool: ON

Model:XFL-TW-2414-24022-22/3095-SP005

Test By:\*\*\*

Temperature:23Deg

Manufacturer:

Assessor:damin

Date:2020-06-12 17:12:06

Humidity:55%

Remarks:

## TM30

