



### Colorimetric Parameters

Chromaticity Coordinate:  $x=0.4692$   $y=0.4096$  /  $u'=0.2690$   $v'=0.5284$   
 CCT=2567K (Duv=-0.0010) Dominant WL:  $\lambda_d = 585.2\text{nm}$  Purity=63.8%  
 Peak WL:  $\lambda_p = 648.1\text{nm}$  FWHM=148.6nm  
 Render Index: Ra=96.8 Render Index: AvgR =97.0  
 R1 =98 R2 =99 R3 =96 R4 =93 R5 =97 R6 =98 R7 =97  
 R8 =97 R9 =99 R10=99 R11=89 R12=99 R13=98 R14=97 R15=99

### Photometric & Radiometric Parameters

Flux=244.1 lm Eff.:51.42 lm/W  $\Phi_e = 1.062\text{ W}$

### Electrical parameters

V=24.00 V I=0.1978 A P=4.747 W PF=1.000 F=0.00 Hz

LEVEL:OUT WHITE:OUT

Status: Integral T = 41 ms  $I_p = 48791$  (74%)

Test Mode: Accuracy Test; Sensitivity = High; Tecool: ON

Model: XFL-TW-2414-24022-22/3095-SP005

Test By:\*\*\*

Temperature:23Deg

Manufacturer:

Assessor:damin

Date:2020-06-12 17:13:11

Humidity:55%

Remarks:

## TM30

