



### Colorimetric Parameters

Chromaticity Coordinate:  $x=0.4756$   $y=0.4103$   $u'=0.2728$   $v'=0.5296$   
 CCT=2492K (Duv=-0.0011) Dominant WL:Ld =585.7nm Purity=65.9%  
 Peak WL:Lp=646.6nm FWHM=144.1nm  
 Render Index:Ra=96.8 Render Index:AvgR =96.8  
 R1 =98 R2 =99 R3 =96 R4 =93 R5 =97 R6 =98 R7 =96  
 R8 =97 R9 =99 R10=99 R11=89 R12=98 R13=98 R14=97 R15=99

### Photometric & Radiometric Parameters

Flux=122.2 lm Eff.:53.43 lm/W Fe=540.5 mW

### Electrical parameters

V=24.00 V I=0.09530 A P=2.287 W PF=1.000 F=0.00 Hz

LEVEL:OUT WHITE:OUT

Status: Integral T = 79 ms Ip = 48499 (74%)  
 Test Mode: Accuracy Test; Sensitivity = High; Tecool: ON

Model:XFL-TW-2414-24022-24/3595-SP005  
 Test By:\*\*\* Date:2020-06-12 16:43:54  
 Temperature:23Deg Humidity:55%  
 Manufacturer: Remarks:  
 Assessor:damin

# TM30

