



Colorimetric Parameters

Chromaticity Coordinate: $x=0.4044$ $y=0.3880$ / $u'=0.2362$ $v'=0.5100$
 CCT=3498K (Duv=-0.0010) Dominant WL: $L_d = 581.3\text{nm}$ Purity=37.8%
 Peak WL: $L_p = 639.5\text{nm}$ FWHM=214.4nm
 Render Index: $R_a = 97.2$ Render Index: AvgR = 96.8
 R1 = 98 R2 = 99 R3 = 97 R4 = 94 R5 = 97 R6 = 98 R7 = 97
 R8 = 97 R9 = 97 R10 = 99 R11 = 90 R12 = 92 R13 = 99 R14 = 98 R15 = 99

Photometric & Radiometric Parameters

Flux=153.7 lm Eff.:63.43 lm/W $F_e = 609.8\text{ mW}$

Electrical parameters

V=24.00 V I=0.1010 A P=2.424 W PF=1.000 F=0.00 Hz

LEVEL:OUT WHITE:ANSI_3500K

Status: Integral T = 87 ms $I_p = 49119$ (75%)

Test Mode: Accuracy Test; Sensitivity = High; Tecool: ON

Model: XFL-TW-2414-24022-24/3595-SP005

Test By: ***

Temperature: 23Deg

Manufacturer:

Assessor: damin

Date: 2020-06-12 16:45:01

Humidity: 55%

Remarks:

TM30

