



### Colorimetric Parameters

Chromaticity Coordinate:  $x=0.4326$   $y=0.3957$  /  $u'=0.2514$   $v'=0.5174$   
 CCT=3005K (Duv=-0.0028) Dominant WL:Ld =583.8nm Purity=48.6%  
 Peak WL:Lp=646.2nm FWHM=189.4nm  
 Render Index:Ra=96.4 Render Index:AvgR =96.2  
 R1 =97 R2 =99 R3 =97 R4 =92 R5 =96 R6 =97 R7 =96  
 R8 =96 R9 =95 R10=98 R11=89 R12=98 R13=97 R14=98 R15=97

### Photometric & Radiometric Parameters

Flux=354.2 lm Eff.:56.40 lm/W Fe=1.470 W

### Electrical parameters

V=24.00 V I=0.2617 A P=6.280 W PF=1.000 F=0.00 Hz

LEVEL:OUT WHITE:ANSI\_3000K

Status: Integral T = 33 ms Ip = 49436 (75%)

Test Mode: Accuracy Test; Sensitivity = High; Tecool: ON

Model:XFL-TW-2419-24022-24/3595-SP005

Test By:  
 Temperature:23Deg  
 Manufacturer:  
 Assessor:damin

Date:2020-06-12 17:01:47  
 Humidity:55%  
 Remarks:

# TM30

