



### Colorimetric Parameters

Chromaticity Coordinate:  $x=0.4017$   $y=0.3861$  /  $u'=0.2353$   $v'=0.5088$   
 CCT=3542K (Duv=-0.0013) Dominant WL:Ld =581.3nm Purity=36.4%  
 Peak WL:Lp=641.5nm FWHM=215.1nm  
 Render Index:Ra=97.0 Render Index:AvgR =96.7  
 R1 =98 R2 =99 R3 =97 R4 =93 R5 =97 R6 =98 R7 =97  
 R8 =97 R9 =97 R10=99 R11=90 R12=93 R13=99 R14=98 R15=98

### Photometric & Radiometric Parameters

Flux=201.0 lm Eff.:61.91 lm/W Fe=797.0 mW

### Electrical parameters

V=24.00 V I=0.1353 A P=3.247 W PF=1.000 F=0.00 Hz

LEVEL:OUT WHITE:ANSI\_3500K

Status: Integral T = 67 ms Ip = 49148 (75%)

Test Mode: Accuracy Test; Sensitivity = High; Tecool: ON

Model:XFL-TW-2419-24022-24/3595-SP005

Test By:  
 Temperature:23Deg  
 Manufacturer:  
 Assessor:damin

Date:2020-06-12 17:00:14  
 Humidity:55%  
 Remarks:

# TM30

