



Colorimetric Parameters

Chromaticity Coordinate: $x=0.4354$ $y=0.4000$ / $u'=0.2513$ $v'=0.5195$
 CCT=2993K (Duv=-0.0014) Dominant WL:Ld =583.4nm Purity=50.7%
 Peak WL:Lp=646.6nm FWHM=190.9nm
 Render Index:Ra=97.0 Render Index:AvgR =96.5
 R1 =100 R2 =98 R3 =95 R4 =94 R5 =98 R6 =98 R7 =96
 R8 =97 R9 =96 R10=96 R11=92 R12=93 R13=99 R14=97 R15=99

Photometric & Radiometric Parameters

Flux=232.2 lm Eff.:65.64 lm/W Fe=945.3 mW

Electrical parameters

V=24.00 V I=0.1474 A P=3.537 W PF=1.000 F=0.00 Hz

LEVEL:OUT WHITE:ANSI_3000K

Status: Integral T = 51 ms Ip = 49088 (75%)

Test Mode: Accuracy Test; Sensitivity = High; Tecool: ON

Model:XFL-US-2403-23822-3095-SP005 Number:1
 Test By: Date:2020-06-24 14:20:54
 Temperature:23Deg Humidity:55%
 Manufacturer:
 Assessor:damin

TM30

