



Colorimetric Parameters

Chromaticity Coordinate: $x=0.4036$ $y=0.3885$ $u'=0.2355$ $v'=0.5101$
 CCT=3519K (Duv=-0.0006) Dominant WL:Ld =581.1nm Purity=37.7%
 Peak WL:Lp=642.6nm FWHM=214.6nm
 Render Index:Ra=97.3 Render Index:AvgR =97.0
 R1 =99 R2 =99 R3 =97 R4 =94 R5 =98 R6 =98 R7 =97
 R8 =98 R9 =99 R10=99 R11=91 R12=92 R13=99 R14=98 R15=99

Photometric & Radiometric Parameters

Flux=283.0 lm Eff.:74.91 lm/W Fe=1.117 W

Electrical parameters

V=24.00 V I=0.1574 A P=3.777 W PF=1.000 F=0.00 Hz

LEVEL:OUT WHITE:ANSI_3500K

Status: Integral T = 48 ms Ip = 49428 (75%)

Test Mode: Accuracy Test; Sensitivity = High; Tecool: ON

Model:XFL-US-2403-23822-3595-SP005 Number:5
 Test By: Date:2020-06-24 14:30:12
 Temperature:23Deg Humidity:55%
 Manufacturer:
 Assessor:damin

TM30

