





**FCC PART 15 SUBPART B CLASS B  
DECLARATION OF CONFORMITY PROCEDURE  
INNOVATION, SCIENCE, AND ECONOMIC DEVELOPMENT  
CANADA ICES-003 ISSUE 6 (JAN. 2016) CLASS B  
TEST REPORT**

For

**Xicato, Inc.**

101 Daggett Dr.  
San Jose, CA 95134 USA

**Model: XIM 19mm**

<b>Report Type:</b> Original Report		<b>Product Type:</b> Intelligent LED Module	
<b>Prepared By</b>	Shoaib Khan Test Engineer 		
<b>Report Number</b>	R1608034		
<b>Report Date</b>	2016-08-26		
<b>Reviewed By</b>	Elijah Garcia EMC Lab / GR 1089 Core Supervisor 		
Bay Area Compliance Laboratories Corp. 1274 Anvilwood Avenue, Sunnyvale, CA 94089, USA Tel: (408) 732-9162 Fax: (408) 732 9164			

Note: This test report was prepared for the customer shown above and for the device described herein. This Test Report is the property of BACL, and shall not be reproduced, except in full, without prior written approval of BACL. This report must not be used by anyone to claim product certification, approval, or endorsement by A2LA, or any agency of the US Government, or any foreign government. NOTE: This test report may contain measurements that were obtained from tests that are outside of our ISO/IEC 17025:2005 Scope of Accreditation. All such test results are marked with an asterisk "\*" within the body of the Test Report.

## TABLE OF CONTENTS

<b>1</b>	<b>GENERAL INFORMATION .....</b>	<b>4</b>
1.1	GENERAL STATEMENTS .....	4
1.2	PURPOSE .....	4
1.3	AGENT FOR THE RESPONSIBLE PARTY .....	4
1.4	RESPONSIBLE PARTY .....	5
1.5	PRODUCT DESCRIPTION OF THE EQUIPMENT UNDER TEST (EUT) .....	5
1.6	MECHANICAL DESCRIPTION OF THE EUT .....	5
1.7	RELATED SUBMITTAL(S)/GRANT(S).....	5
1.8	TEST METHODOLOGY .....	5
1.9	TEST FACILITY REGISTRATIONS .....	6
1.10	TEST FACILITY ACCREDITATIONS.....	6
1.11	MEASUREMENT UNCERTAINTIES .....	9
<b>2</b>	<b>SYSTEM TEST CONFIGURATION .....</b>	<b>10</b>
2.1	JUSTIFICATION.....	10
2.2	EUT EXERCISING SOFTWARE .....	10
2.3	EQUIPMENT MODIFICATIONS .....	10
2.4	SPECIAL EQUIPMENT .....	10
2.5	EUT MODE OF OPERATION.....	10
2.6	METHOD OF MONITORING .....	10
2.7	LOCAL SUPPORT EQUIPMENT.....	10
2.8	REMOTE SUPPORT EQUIPMENT .....	10
2.9	EUT INTERNAL CONFIGURATION DETAILS.....	11
2.10	EXTERNAL I/O CABLING LIST AND DETAILS .....	11
2.11	EUT EXTERNAL POWER SUPPLY LIST AND DETAILS .....	11
<b>3</b>	<b>SUMMARY OF TEST RESULTS.....</b>	<b>12</b>
<b>4</b>	<b>FCC §15.109 &amp; ISSED ICES-003 ISSUE 6 (JAN. 2016) – RADIATED EMISSIONS.....</b>	<b>13</b>
4.1	APPLICABLE STANDARDS .....	13
4.2	TEST SETUP BLOCK DIAGRAM.....	16
4.3	CORRECTED AMPLITUDE AND MARGIN CALCULATIONS.....	16
4.4	TEST EQUIPMENT LIST AND DETAILS .....	17
4.5	EMI MEASUREMENT SOFTWARE .....	17
4.6	TEST ENVIRONMENTAL CONDITIONS & TEST PERSONNEL .....	17
4.7	RADIATED EMISSIONS TEST PLOTS AND DATA.....	18
4.8	SUMMARY OF TEST RESULTS.....	20
<b>5</b>	<b>EXHIBIT A – FCC AND INDUSTRY CANADA PRODUCT LABELING REQUIREMENTS.....</b>	<b>21</b>
5.1	AS PER FCC §15.19: LABELLING REQUIREMENTS PARAGRAPH 3 .....	21
5.2	AS PER ISSED ICES-003 §8 LABELING REQUIREMENTS .....	22
5.3	LABEL LOCATION ON EUT .....	22
<b>6</b>	<b>EXHIBIT B- TEST SETUP PHOTOS .....</b>	<b>23</b>
6.1	RADIATED EMISSIONS.....	23
<b>7</b>	<b>EXHIBIT C- EUT PHOTOS.....</b>	<b>25</b>
7.1	EUT FRONT VIEW .....	25
7.2	EUT RIGHT VIEW .....	25
7.3	EUT REAR VIEW .....	26
7.4	EUT LEFT VIEW .....	26
7.5	EUT STAND VIEW .....	27
7.6	MAIN EUT TOP VIEW.....	27
7.7	EUT MAIN BOARD VIEW.....	28

**DOCUMENT REVISION HISTORY**

<b>Revision Number</b>	<b>Report Number</b>	<b>Description of Revision</b>	<b>Date of Revision</b>
0	R1608034	Original Report	2016-08-26

# 1 General Information

---

## 1.1 General Statements

Bay area Compliance Laboratory Corp. [BACL] hereby makes the following Statements:

- The Unit(s) described in this Test Report were received at BACL's facilities on 03 August 2016. Testing was performed on the Unit(s) described in this Test Report during the period 03 August 2016.
- The Test Results reported herein apply only to the Unit(s) actually tested, and to substantially identical Units.
- This Test Report must not be used to claim product endorsement by A2LA, or any agency of the U.S. Government, or by any other foreign government.
- This Test Report is the property of BACL, and shall not be reproduced, except in full, without prior written approval of BACL.

## 1.2 Purpose

The purpose of this Test Report is to document the compliance of *the product: Intelligent LED Module, model: XIM 9mm* to the requirements of 47 CFR Part 15 Subpart B for Class B Devices and Innovation, Science, and Economic Development Canada ICES-003 Issue 6 (Jan. 2016) for Class B Devices. The objective of the testing performed was to determine the compliance of the EUT in accordance with the FCC Rules (i.e., 47 CFR Part 15 Subpart B Sections 15.107 and 15.109) using the CISPR 22 Edition 3 Class B limits for conducted and radiated emissions, ICES-003 Issue 6 (Jan. 2016) per Section 6.1 Table 2 for powerline conducted emissions limits; per Section 6.2.1 Table 5 for Radiated Emissions at frequencies below 1 GHz; and, per Section 6.2.2 Table 7 for Radiated Emissions at frequencies above 1 GHz, subject to the upper frequency limitations stated in Section 6.2 Table 3, using the test methods in the latest version of ANSI C63.4 (i.e., ANSI C63.4-2014). This Test Report references the applicable Electromagnetic Emissions requirements.

THE DATA CONTAINED IN THIS TEST REPORT WAS COLLECTED AND COMPILED BY:



---

Shoaib Khan  
[Test Engineer]

## 1.3 Agent for the Responsible Party

None

## 1.4 Responsible Party

Company Name: Xicato, Inc.  
Contact: Robert Yang  
Street Address: 101 Daggett Dr.  
City/State/Zip: San Jose, CA 95134  
Country: USA  
Telephone: +1-408-599-0448  
Fax: +1-408-890-2817 (main)  
E-mail: Robert.yang@xicato.com  
Web: <http://www.xicato.com/>

## 1.5 Product Description of the Equipment under Test (EUT)

The “EUT” (Equipment under Test) was a LED light with integrated driver and Bluetooth communication

## 1.6 Mechanical Description of the EUT

**Dimensions:** approximately 8.0 cm (L) x 13.0 cm (W) x 13.0 cm (H)

**Weight:** approximately 0.55 kilogrammes.

**Serial Number:** None. *(Note: The EUT was a pre-production prototype that had no Serial Number).*

**EUT Photos:** See Exhibit C of this Test Report.

## 1.7 Related Submittal(s)/Grant(s)

None

## 1.8 Test Methodology

All of the measurements contained in this Test Report were made in accordance with ANSI C63.4-2014 “American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz”. All tests were performed at the Bay Area Compliance Laboratories Corp. facilities in Sunnyvale California.

## 1.9 Test Facility Registrations

BACLs test facilities that are used to perform Radiated and Conducted Emissions tests are currently recognized by the Federal Communications Commission as Accredited with NIST Designation Number US1129.

BACL's test facilities that are used to perform Radiated and Conducted Emissions tests are currently registered with Industry Canada under Registration Numbers: 3062A-1, 3062A-2, and 3062A-3.

BACL is a Chinese Taipei Bureau of Standards Metrology and Inspection (BSMI) validated Conformity Assessment Body (CAB), under Appendix B, Phase I Procedures of the APEC Mutual Recognition Arrangement (MRA). BACL's BSMI Lab Code Number is: SL2-IN-E-1002R

BACL's test facilities that are used to perform AC Line Conducted Emissions, Telecommunications Line Conducted Emissions, Radiated Emissions from 30 MHz to 1 GHz, and Radiated Emissions from 1 GHz to 6 GHz are currently recognized as Accredited in accordance with the Voluntary Control Council for Interference [VCCI] Article 15 procedures under Registration Number A-0027.

## 1.10 Test Facility Accreditations

Bay Area Compliance Laboratories Corp. (BACL) is:

**A- An independent, 3<sup>rd</sup>-Party, Commercial Test Laboratory accredited to ISO/IEC 17025:2005 by A2LA (Test Laboratory Accreditation Certificate Number 3279.02),** in the fields of: Electromagnetic Compatibility and Telecommunications. Unless noted by an Asterisk (\*) in the Compliance Matrix (See Section 3 of this Test Report), BACL's ISO/IEC 17025:2005 Scope of Accreditation includes all of the Test Method Standards and/or the Product Family Standards detailed in this Test Report..

BACL's ISO/IEC 17025:2005 Scope of Accreditation includes a comprehensive suite of EMC Emissions, EMC Immunity, Radio, RF Exposure, Safety and wireline Telecommunications test methods applicable to a wide range of product categories. These product categories include Central Office Telecommunications Equipment [including NEBS - Network Equipment Building Systems], Unlicensed and Licensed Wireless and RF devices, Information Technology Equipment (ITE); Telecommunications Terminal Equipment (TTE); Medical Electrical Equipment; Industrial, Scientific and Medical Test Equipment; Professional Audio and Video Equipment; Industrial and Scientific Instruments and Laboratory Apparatus; Cable Distribution Systems, and Energy Efficient Lighting.

**B- A Product Certification Body accredited to ISO/IEC 17065:2012 by A2LA (Product Certification Body Accreditation Certificate Number 3279.03) to certify**

- For the USA (Federal Communications Commission):

- 1- All Unlicensed radio frequency devices within FCC Scopes A1, A2, A3, and A4;
- 2- All Licensed radio frequency devices within FCC Scopes B1, B2, B3, and B4;
- 3- All Telephone Terminal Equipment within FCC Scope C.

- For the Canada (Industry Canada):

- 1 All Scope 1-Licence-Exempt Radio Frequency Devices;
- 2 All Scope 2-Licensed Personal Mobile Radio Services;
- 3 All Scope 3-Licensed General Mobile & Fixed Radio Services;
- 4 All Scope 4-Licensed Maritime & Aviation Radio Services;
- 5 All Scope 5-Licensed Fixed Microwave Radio Services
- 6 All Broadcasting Technical Standards (BETS) in the Category I Equipment Standards List.

- For Singapore (Info-Communications Development Authority (IDA)):

- 1 All Line Terminal Equipment: All Technical Specifications for Line Terminal Equipment – Table 1 of IDA MRA Recognition Scheme: 2011, Annex 2
  2. All Radio-Communication Equipment: All Technical Specifications for Radio-Communication Equipment – Table 2 of IDA MRA Recognition Scheme: 2011, Annex 2
- For the Hong Kong Special Administrative Region:
- 1 All Radio Equipment, per KHCA 10XX-series Specifications;
  - 2 All GMDSS Marine Radio Equipment, per HKCA 12XX-series Specifications;
  - 3 All Fixed Network Equipment, per HKCA 20XX-series Specifications.
- For Japan:
- 1 MIC Telecommunication Business Law (Terminal Equipment):
    - All Scope A1 - Terminal Equipment for the Purpose of Calls;
    - All Scope A2 - Other Terminal Equipment
  - 2 Radio Law (Radio Equipment):
    - All Scope B1 - Specified Radio Equipment specified in Article 38-2-2, paragraph 1, item 1 of the Radio Law
    - All Scope B2 - Specified Radio Equipment specified in Article 38-2-2, paragraph 1, item 2 of the Radio Law
    - All Scope B3 - Specified Radio Equipment specified in Article 38-2-2, paragraph 1, item 3 of the Radio Law

**C- A Product Certification Body accredited to ISO/IEC 17065:2012 by A2LA (Product Certification Body Accreditation Certificate Number 3279.01) to certify Products to USA's Environmental Protection Agency (EPA) ENERGY STAR Product Specifications for:**

- 1 Electronics and Office Equipment:
  - for Telephony (ver. 3.0)
  - for Audio/Video (ver. 3.0)
  - for Battery Charging Systems (ver. 1.1)
  - for Set-top Boxes & Cable Boxes (ver. 4.1)
  - for Televisions (ver. 6.1)
  - for Computers (ver. 6.0)
  - for Displays (ver. 6.0)
  - for Imaging Equipment (ver. 2.0)
  - for Computer Servers (ver. 2.0)
- 2 Commercial Food Service Equipment
  - for Commercial Dishwashers (ver. 2.0)
  - for Commercial Ice Machines (ver. 2.0)
  - for Commercial Ovens (ver. 2.1)
  - for Commercial Refrigerators and Freezers
- 3 Lighting Products
  - For Decorative Light Strings (ver. 1.5)
  - For Luminaires (including sub-components) and Lamps (ver. 1.2)
  - For Compact Fluorescent Lamps (CFLs) (ver. 4.3)
  - For Integral LED Lamps (ver. 1.4)
- 4 Heating, Ventilation, and AC Products
  - for Residential Ceiling Fans (ver. 3.0)
  - for Residential Ventilating Fans (ver. 3.2)
- 5 Other
  - For Water Coolers (ver. 3.0)

**D- A NIST Designated Phase-I and Phase-II Conformity Assessment Body (CAB) for the following economies and regulatory authorities under the terms of the stated MRAs/Treaties:**

- Australia: ACMA (Australian Communication and Media Authority) – APEC Tel MRA -Phase I;
- Canada: (Industry Canada - IC) Foreign Certification Body – FCB – APEC Tel MRA -Phase I & Phase II;
- Chinese Taipei (Republic of China – Taiwan):
  - o BSMI (Bureau of Standards, Metrology and Inspection) APEC Tel MRA -Phase I;
  - o NCC (National Communications Commission) APEC Tel MRA -Phase I;
- European Union:
  - o EMC Directive 2004/108/EC US-EU EMC & Telecom MRA CAB
  - o Radio & Teleterminal Equipment (R&TTE) Directive 1995/5/EC  
US -EU EMC & Telecom MRA CAB
- Hong Kong Special Administrative Region: (Office of the Telecommunications Authority – OFTA)  
APEC Tel MRA -Phase I & Phase II
- Israel – US-Israel MRA Phase I
- Republic of Korea (Ministry of Communications - Radio Research Laboratory) APEC Tel MRA -Phase I
- Singapore: (Infocomm Development Authority - IDA) APEC Tel MRA -Phase I & Phase II;
- Japan: VCCI - Voluntary Control Council for Interference US-Japan Telecom Treaty VCCI Side Letter-
- USA:
  - o ENERGY STAR Recognized Test Laboratory – US EPA
  - o Telecommunications Certification Body (TCB) – US FCC;
- Vietnam: APEC Tel MRA -Phase I;



## 1.11 Measurement Uncertainties

All measurements involve uncertainties. In the case of EMC Emissions tests, the influence quantities (factors) that make a significant contribution to the measurement uncertainties are detailed in the latest version of CISPR 16-4-2 “Specification for radio disturbance and immunity measuring apparatus and methods – Part 4-2: Uncertainties, statistics and limit modelling – Measurement instrumentation uncertainty” (i.e., CISPR 16-4-2:2011-06 + C1:2013-04 +A1:2014-02).

Based on the uncertainty models given in the latest version of CISPR16-4-2, and, based on the calibration uncertainties of the specific instruments and facilities used at BACL to perform the measurements documented in this Test Report, the following estimates have been made of BACL’s Measurement Uncertainties for the measurements documented in this Test Report.

Type of Measurement	BACL Typical $U_{LAB}$ Value (for a k=2 Coverage Factor, equivalent to ~ 95% level of confidence)	$U_{CISPR}$ Value worst-allowable values, per Table 1 of the latest version of CISPR 16-4-2 (for a k=2 Coverage Factor, equivalent to ~ 95% level of confidence)
Conducted Disturbance (Mains Port) 150 kHz to 30 MHz (i.e., AC/DC Line Conducted Emissions measurements made with a Fischer FCC-LISN-50-25-2-10 LISN)	2.26	3.44 dB
Radiated Electric Field Disturbance – Horizontal Polarization, 30 MHz – 200 MHz (i.e., Radiated Emissions measured at 10 metres distance)	4.21 dB	5.05 dB
Radiated Electric Field Disturbance – Vertical Polarization, 30 MHz – 200 MHz (i.e., Radiated Emissions measured at 10 metres distance)	4.07 dB	5.03 dB
Radiated Electric Field Disturbance – Horizontal Polarization, 200 MHz – 1000 MHz (i.e., Radiated Emissions at 10 metres distance)	4.17 dB	5.21 dB
Radiated Electric Field Disturbance – Vertical Polarization, 200 MHz – 1000 MHz z (i.e., Radiated Emissions measured at 10 metres distance)	4.46 dB	5.22 dB
Radiated Electric Field Disturbance Horizontal & Vertical Polarizations, 1 GHz – 6 GHz (i.e., Radiated Emissions measured at 3 metres distance)	4.62 dB (With Boresighting)	$U_{CISPR}$ Value is Not Specified
Radiated Electric Field Disturbance Horizontal & Vertical Polarizations, 6 GHz – 18 GHz (i.e., Radiated Emissions measured at 3 metres distance)	4.67 dB (With Boresighting)	$U_{CISPR}$ Value is Not Specified

## 2 System Test Configuration

### 2.1 Justification

The EUT and its Support Equipment were configured as a system and were arranged in accordance with the ANSI C63.4-2014 Standard.

### 2.2 EUT Exercising Software

The software (XIMtroller) used was provided by Robert Yang and was GUI based featuring Microsoft Windows and Apple IOS.

### 2.3 Equipment Modifications

None

### 2.4 Special Equipment

None

### 2.5 EUT Mode of Operation

The EUT was emitting light at Full intensity powered by 48 V DC.

### 2.6 Method of Monitoring

Power on; connect to EUT and verify communication.

### 2.7 Local Support Equipment

The following items of Support Equipment were located locally (i.e., within the Semi-Anechoic Chamber):

Manufacturer	Description	Model	Serial Number
ROAL living Energy	AC/DC Power Supply	Strato RSLP035-48	323K0A73214A000047
Apple	Cell phone	iPhone SE	-

### 2.8 Remote Support Equipment

Manufacturer	Description	Model	Serial Number
-	-	-	-

**2.9 EUT Internal Configuration Details**

Manufacturer	Description	Model	Serial Number
Xicato, Inc.	Main Board	2001-00X0-2671 Rev 02	-

**2.10 External I/O Cabling List and Details**

Cable Descriptions	Length (m)	From	To
-	-	-	-

**2.11 EUT External Power Supply List and Details**

None

### 3 Summary of Test Results

<b>FCC (47 CFR Part 15 Subpart B) &amp; ISED ICES-003 Issue 6 (Jan. 2016) RULES</b>	<b>Descriptions of Test</b>	<b>Result(s)</b>
FCC §15.107 & ICES-003 Issue 6 (Jan. 2016) Section 6.1 Table 2	Conducted Emissions	N/A
FCC §15.109 & CAN/CSA-CISPR 22-10 Table 6 and ICES-003 Issue 6 (Jan. 2016) Section 6.2.2 Table 7	Radiated Emissions	Pass

N/A: The EUT is DC powered.

## 4 FCC §15.109 & ISED ICES-003 Issue 6 (Jan. 2016) – Radiated Emissions

### 4.1 Applicable Standards

#### As per FCC §15.109: Radiated Emission Limits

a) Except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency of emission (MHz)	Field strength (microvolts/meter)
30-88	100
88-216	150
216-960	200
Above 960	500

(g) As an alternative to the radiated emission limits shown in paragraphs (a) and (b) of this section, digital devices may be shown to comply with the standards contained in Third Edition of the International Special Committee on Radio Interference (CISPR), Pub. 22, “Information Technology Equipment—Radio Disturbance Characteristics—Limits and Methods of Measurement” (incorporated by reference, *see* §15.38). In addition:

- (1) The test procedure and other requirements specified in this part shall continue to apply to digital devices.
- (2) If, in accordance with §15.33 of this part, measurements must be performed above 1000 MHz, compliance above 1000 MHz shall be demonstrated with the emission limit in paragraph (a) or (b) of this section, as appropriate. Measurements above 1000 MHz may be performed at the distance specified in the CISPR 22 publications for measurements below 1000 MHz provided the limits in paragraphs (a) and (b) of this section are extrapolated to the new measurement distance using an inverse linear distance extrapolation factor (20 dB/decade), e.g., the radiated limit above 1000 MHz for a Class B digital device is 150  $\mu\text{V/m}$ , as measured at a distance of 10 meters.
- (3) The measurement distances shown in CISPR Pub. 22, including measurements made in accordance with this paragraph above 1000 MHz, are considered, for the purpose of §15.31(f)(4) of this part, to be the measurement distances specified in this part.

*Note: The CISPR 22 Third Edition Class B Radiated Emissions Limits were applied from 30 MHz to 1 GHz (i.e., from 30 MHz to 230 MHz, a Limit of 30 dB $\mu\text{V/m}$  was applied at a 10 m measurement distance; from 230 MHz to 1000 MHz, a 37 dB $\mu\text{V/m}$  limit was applied at a 10 m measurement distance). Above 1000 MHz, the FCC limit of 500  $\mu\text{V/m}$  (54 dB $\mu\text{V/m}$ ) was applied at a 3 m measurement distance.*

**As per the Innovation, Science, and Economic Development Canada ICES-003 Issue 6 (Jan. 2016) Section 6.2 Table 3 Frequency Limits for Radiated Emissions:**

Radiated emissions from an ITE shall be measured from the lowest frequency generated, or used, in the device or 30 MHz, whichever is higher, up to the frequency determined in accordance with Table 3.

<b>Table 3 – Frequency Range of Measurement Highest Frequency Generated or Used in Device</b>	<b>Upper Frequency of Radiated Measurement</b>
Below 1.705 MHz	No radiated testing required
1.705 MHz – 108 MHz	1 GHz
108 MHz – 500 MHz	2 GHz
500 MHz – 1 GHz	5 GHz
Above 1 GHz	5th harmonic of the highest frequency or 40 GHz, whichever is lower.

At frequencies at or above 30 MHz, measurements may be performed at a distance other than what is specified in this Section. Measurements are not made in the near field except where it can be shown that near field measurements are appropriate due to the characteristics of the device; and it can be demonstrated that the signal levels needed to be measured at the distance employed can be detected by the measurement equipment. Measurements shall not be performed at a distance greater than 30 meters unless it can be demonstrated that measurements at a distance of 30 meters or less are not practical. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB per decade (inverse linear-distance for field strength measurements).

**As per the Innovation, Science, and Economic Development Canada ICES-003 Issue 6 (Jan. 2016) Section 5(a) (ii) (i.e., CAN/CSA-CISPR 22-10 Class B Radiated Emissions Limits:**

**CAN/CSA-CISPR 22-10 Class B Radiated Emissions Limits as stated in  
Table 6 – Limits for radiated disturbance of class B ITE at a measuring distance of 10 m**

<b>Frequency (MHz)</b>	<b>Class B Radiated Limit (dB<math>\mu</math>V/m) Quasi-Peak Detector</b>
30 to 230	30
230 to 1000	37
NOTE 1 The lower limit shall apply at the transition frequency. NOTE 2 Additional provisions may be required for cases where interference occur	

**As per the Innovation, Science, and Economic Development Canada ICES-003 Issue 6 (Jan. 2016) Section 6.2.2 Table 7 Class B Radiated Emissions Limits above 1 GHz:**

**Class B:** An ITE that does not meet the conditions for Class A equipment shall comply with the Class B radiated limits set out in Table 7 determined at a distance of 3 meters.

**Table 7 – Class B Radiated Limits above 1 GHz Frequency (MHz)**

Frequency (MHz)	Class B Radiated Limit (dB $\mu$ V/m)	
	Linear Average Detector	Peak Detector
> 1000	54	74

The radiated emissions tests were performed in the BACL 10-meter Anechoic Chamber, using a test setup in accordance with ANSI C63.4-2014 measurement procedures.

SPECIAL NOTE: A “Boresight Mast” was used to ensure that the emissions from the EUT remained within the 3 dB Beamwidth of the Double-Ridge Guide Horn Antenna used to make measurements above 1 GHz. Additionally, at frequencies above 1 GHz, loose-laid RF Absorber was placed on the Chamber Ground Plane to ensure that those measurements were made under conditions that approximated free-space.

The spacing between the peripherals (if any) was 10 cm.

The external I/O cables (if any) were draped along the test table and bundled as required.


The procedures detailed in ANSI C63.4-2014 Clauses 8.3.1 and 11.9.2, were used to determine the mode of operation and cable positions of the EUT system that produce the emissions with the highest amplitudes relative to the limit. This arrangement was used when the final ac radiated emissions measurements were made on the EUT.

Using the mode of operation and cable position arrangement of the EUT system determined in ANSI C63.4-2014 Clause 8.3.1, the procedure detailed in ANSI C63.4-2014 Clause 11.9.3 was used to perform the final radiated emission measurements. In particular, the six highest emissions relative to the limit in the frequency range were recorded.

It should be noted that, in addition to cable manipulations, a maximizing procedure that included varying the receive antenna height and the turntable azimuth was employed while making all final compliance measurements on the EUT.

All measurement data was initially collected and recorded under computer control using the VASONA<sup>®</sup> EMI Software package, with the EMI Receiver/Spectrum Analyzer in Peak Detection mode. From 30 MHz to 1 GHz, Quasi-peak measurements were made only when a Peak emission was found to be - 6 dB or higher with respect to the applicable specification limits. Above 1 GHz, both Peak and CISPR (Linear) Average measurement were collected and recorded under computer control using the VASONA<sup>®</sup> EMI Software package.

## 4.2 Test Setup Block Diagram



## 4.3 Corrected Amplitude and Margin Calculations

The Corrected Amplitude (CA) was calculated by adding the Antenna Factor (AF), the Cable Loss (CL), the Attenuator and RF Limiter Loss Factor (AL) to the “raw” Amplitude (Am) reading, and then subtracting the Preamplifier Gain (Gp). The basic equation is as follows:

$$CA = Am + AF + CL + AL - Gp$$

For example, if (at some frequency and measurement distance) we had a measured Amplitude reading (Am) of 50.0 dBμV/m, an Antenna Factor of 17.0 dB/m, a Cable Loss (CL) of 5.8 dB, an Attenuator and RF Limiter Loss (AL) of 0.4 dB, and a Preamplifier Gain of 32.5 dB, the corrected amplitude (CA) would be 40.7 dBμV/m (i.e.,  $50.0 + 17.0 + 5.8 + 0.4 - 32.5 = 40.7$  dBμV/m).

The “**Margin**” values in the following data tables indicate the degree of compliance within the applicable limit. For example, a margin of -7 dB means the emission is 7 dB below the applicable Limit. The equation for the margin calculation is as follows:

$$\text{Margin (dB)} = \text{Corrected Amplitude (dB}\mu\text{V/m)} - \text{Applicable Limit (dB}\mu\text{V/m)}$$



#### 4.4 Test Equipment List and Details

BACL Asset #	Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Interval
711	Keysight Technologies	RF Limiter	11867A	MY42242931	2015-12-15	1 year
322	Rohde & Schwarz	Receiver, EMI Test	ESCI 1166.5950K 03	100337	2015-06-18	2 years
311	Sunol Sciences	Controller, System	SC104V	113005-1	Cal. Not required	Cal. Not required
321	Sunol Sciences	Antenna, BiConiLog	JB3	A020106-2	2015-07-11	2 years
287	Agilent	Analyzer, Spectrum	E4446A	US44300386	2015-10-22	1 year
473	EMCO	Horn Antenna	3115	9511-4627	2016-01-28	2 years
606	UTiFLEX	SMA Cable	64638	218625007	2016-06-17	1 year
601	UTiFLEX	High Frequency Cable	223458-002	223458-001	2016-06-06	1 year
690	Wireless Solutions	N-Type Coax Cable	LMR 400	690	2015-07-02	1 year

**Statement of Traceability:** BACL Corp. attests that all of the calibrations on the equipment items listed above were traceable to NIST or to another internationally recognized National Metrology Institute (NMI), and were compliant with A2LA Policy P102 (dated 14 May 2015) “A2LA Policy on Metrological Traceability”.

#### 4.5 EMI Measurement Software


The EMI Measurement software package used to perform this test was the EMIsoft<sup>®</sup> VASONA<sup>®</sup> Version 6.00.

#### 4.6 Test Environmental Conditions & Test Personnel

<b>Test Date(s)</b>	2016-08-03
<b>Test Site</b>	10m Chamber 1
<b>Temperature:</b>	23° C
<b>Relative Humidity:</b>	44%
<b>Barometric Pressure:</b>	101.7 kPa
<b>Test Personnel:</b>	Shoaib Khan

## 4.7 Radiated Emissions Test Plots and Data

### 30-1000 MHz Peak Pre-Scan (measured at a 10 meter distance) Plot




### Quasi-Peak Measurements:

Frequency (MHz)	Corrected Amplitude (dBμV/m)	Test Antenna		Turntable Azimuth (degrees)	Limit (dBμV/m)	Margin (dB)
		Height (cm)	Polarity (H/V)			
31.08	18.56	348	H	281	30	-11.44
74.15	16.75	368	V	32	30	-13.25
117.03	16.31	222	V	103	30	-13.69
990.22	22.63	265	V	345	37	-14.37
40.48	13.94	393	V	226	30	-16.06

Note: Other peak values were 20dB below the Quasi-peak limit therefore no additional measurements were performed.

### 1-13 GHZ Peak Pre-scan (measured at a 3 meter distance) Plot



### Peak Measurements

Frequency (MHz)	Corrected Amplitude (dB $\mu$ V/m)	Antenna Height (cm)	Polarity (H/V)	Turntable Azimuth (degrees)	Limit (dB $\mu$ V/m)	Margin (dB)
11913	56.51	106	V	359	74	-17.49
10080	56.14	186	V	258	74	-17.86
2072	43.6	110	H	134	74	-30.4

### Average Measurements

Frequency (MHz)	Corrected Amplitude (dB $\mu$ V/m)	Antenna Height (cm)	Polarity (H/V)	Turntable Azimuth (degrees)	Limit (dB $\mu$ V/m)	Margin (dB)
10080	45.88	186	V	258	54	-8.12
11913	45.42	106	V	359	54	-8.58
2072	32.82	110	H	134	54	-21.18

#### 4.8 Summary of Test Results

Based upon the measurements made, it was determined that the EUT complied with the applicable FCC Part 15 Subpart B Class B and ISED ICES-003 Issue 6 (Jan. 2016) Class B Radiated Emissions Limits. The EUT's worst margin reading was:

<b>FCC 15B &amp; ISED ICES-003 Issue 6 (Jan. 2016) Radiated Emissions - Worst Case (30 MHz – 1 GHz):</b>			
<b>Frequency (MHz)</b>	<b>Polarization (Horizontal Vertical)</b>	<b>Highest Amplitude Quasi-Peak Corrected Amplitude (dB<math>\mu</math>V/m)</b>	<b>Worst-Case Quasi-Peak Margin (dB)</b>
31.08	Horizontal	18.56	-11.44

<b>FCC 15B &amp; ISED ICES-003 Issue 6 (Jan. 2016) Radiated Emissions – Peak Worst Case (Above 1 GHz):</b>			
<b>Frequency (MHz)</b>	<b>Polarization (Horizontal / Vertical)</b>	<b>Highest Peak Corrected Amplitude (dB<math>\mu</math>V/m)</b>	<b>Worst-Case Peak Margin (dB)</b>
11913	Vertical	56.51	-17.49

<b>FCC15B &amp; ISED ICES-003 Issue 6 (Jan. 2016) Radiated Emissions – CISPR Average Worst Case (Above 1 GHz):</b>			
<b>Frequency (MHz)</b>	<b>Polarization (Horizontal / Vertical)</b>	<b>Highest CISPR Average Corrected Amplitude (dB<math>\mu</math>V/m)</b>	<b>Worst-Case CISPR Average Margin (dB)</b>
10080	Vertical	45.88	-8.12

## 5 Exhibit A – FCC and Industry Canada Product Labeling Requirements

### 5.1 As per FCC §15.19: Labelling Requirements Paragraph 3

(3) All other devices shall bear the following statement in a conspicuous location on the device:



This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Specifications: Text is white in color and is left justified. Labels are printed in indelible ink on permanent adhesive backing or silk-screened and shall be affixed at a conspicuous location on the EUT.

### As per FCC §15.105: Information to the User

(b) For a Class B digital device or peripheral, the instructions furnished the user shall include the following or similar statement, placed in a prominent location in the text of the manual:

NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

## 5.2 As per ISED ICES-003 §8 Labeling Requirements

The manufacturer, importer or supplier shall meet the labeling requirements set out in this section and in Notice 2014-DRS1003 for electronic labelling for every unit

- (i) Prior to marketing in Canada, for ITE manufactured in Canada, and;
- (ii) Prior to importation into Canada, for imported ITE.

Each unit of an ITE model shall bear a label (see below) that represents the manufacturer's or the importer's SDoC with Innovation, Science and Economic Development Canada's ICES-003. This label shall be permanently affixed to the ITE or displayed electronically and its text must be clearly legible. If the dimensions of the device are too small or if it is not practical to place the label on the ITE and electronic labelling has not been implemented, the label shall be, upon agreement with Innovation, Science and Economic Development Canada, placed in a prominent location in the user manual supplied with the ITE. The user manual may be in an electronic format and must be readily available.

### As per ISED ICES-003 §8

Innovation, Science, and Economic Development Canada ICES-003 Compliance Label:

**CAN ICES-3 (B)/NMB-3(B)**

## 5.3 Label Location on EUT




## 6 Exhibit B- Test Setup Photos

### 6.1 Radiated Emissions

30 MHz to 1000 MHz, Front View




30 MHz to 1000 MHz, Rear View






1 GHz to 13 GHz, Front View




1 GHz to 13 GHz, Rear View






## 7 Exhibit C- EUT Photos

### 7.1 EUT Front View



### 7.2 EUT Right View



### 7.3 EUT Rear View




### 7.4 EUT Left View




## 7.5 EUT Stand View



## 7.6 Main EUT Top View



## 7.7 EUT Main Board View



---END OF REPORT ---